



# Document Manager

- Full multifunctionality including colour scan for increased efficiency
- Total data security with Toshiba's unique secure hard disc drive to protect your documents from unauthorised access
- Latest Toshiba e-BRIDGE technology to ensure reliable quality and ease of use
- Internal toner recycling and low power consumption for maximum eco-efficiency

**e-STUDIO256SE**  
**e-STUDIO306SE**



SAP® Printer Vendor Solution





**e-STUDIO256SE**  
**e-STUDIO306SE**



<p><b>General</b></p>	<p><b>Print &amp; Copy Speed</b> 25/30 ppm (A4) 16/16 ppm (A3)</p> <p><b>Warm-up Time</b> Approx. 20 seconds</p> <p><b>Paper Size &amp; Weight</b> Cassettes: A5R-A3, 64-105 g/m<sup>2</sup> Large Capacity Feeder<sup>1)</sup>: A4, 64-105 g/m<sup>2</sup> Bypass: A5R-A3, 52-209 g/m<sup>2</sup></p> <p><b>Paper Capacity</b> 2 x 550 sheets (Cassettes), 100 sheets (Bypass)</p> <p><b>Automatic Duplex Inner Output Tray</b> A5R-A3, 64-105 g/m<sup>2</sup></p> <p><b>Controller Type</b> 550-sheet capacity</p> <p><b>Control Panel</b> Toshiba e-BRIDGE</p> <p><b>Memory Interface</b> Tilttable with 9" (22.8 cm) colour LCD touch screen</p> <p><b>Dimensions &amp; Weight</b> Toshiba Secure HDD 160 GB<sup>2)</sup>, 1 GB RAM 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN<sup>1)</sup> (IEEE802.11b/g), Bluetooth<sup>1)</sup> 575 x 586 x 756 mm (W x D x H), ~ 59 kg</p>
<p><b>Print</b></p>	<p><b>Resolution</b> Max. 2,400 x 600 dpi with smoothing</p> <p><b>Page Description Languages Supported Systems</b> XPS, PCL6 and PostScript 3 compatible Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400</p> <p><b>Print Functions</b> Universal Driver, Driver templates, Driver plug-ins, Private/Hold print, Print from USB, Tandem printing, etc.</p>
<p><b>Scan</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi, 8 bit per colour channel</p> <p><b>Scan Speed</b> Colour &amp; B&amp;W: up to 43/57 ipm (300 dpi)</p> <p><b>Scan Modes</b> Auto-Colour (ACS), Colour, Greyscale, B&amp;W</p> <p><b>File Formats</b> JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, Searchable PDF<sup>1)</sup> (and other formats like DOC, XLS, RTF, TXT, PDF/A)<sup>1)</sup></p> <p><b>Scan Functions</b> WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan<sup>1)</sup>, Scan to Box (e-Filing), TWAIN 1.7/1.8/1.9</p>
<p><b>Copy</b></p>	<p><b>Resolution</b> Scan: 600 x 600 dpi</p> <p><b>First Copy Output Time</b> Print: 2,400 x 600 dpi with smoothing</p> <p><b>Zoom</b> Approx. 4.7 seconds</p> <p><b>Copy Modes</b> 25-400% (platen), 25-200% (RADF)<sup>1)</sup> Text, Text/Photo, Photo, Colour Document, Custom</p>
<p><b>Fax<sup>1)</sup></b></p>	<p><b>Communication</b> Super G3, G3 - (opt. 2<sup>nd</sup> line), Internet Fax T.37</p> <p><b>Transmission Speed</b> Approx. 3 seconds per page</p> <p><b>Compression</b> JBIG, MMR, MR, MH</p> <p><b>Fax Memory</b> 1 GB (HDD) Transmission/Reception</p> <p><b>Network-Fax</b> Driver for Windows 7/Vista/XP (32/64 bit), etc.</p> <p><b>Incoming Fax Routing</b> To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing</p>
<p><b>System &amp; Security</b></p>	<p><b>Device Management</b> e-BRIDGE Fleet Management System<sup>1)</sup>, TopAccess for remote administration and configuration</p> <p><b>System Features</b> e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, RIP-while-Print, e-BRIDGE Open Platform<sup>1)</sup>, Embedded Web Browser, Job Skip</p> <p><b>Accounting &amp; Security</b> Role Based Access, LDAP support, 1,000 department codes &amp; 10,000 user codes, card reader<sup>1)</sup>, Quota management, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler<sup>1)</sup>, IP and MAC address filter, port filter, support of SSL and IPsec<sup>1)</sup> protocols, IEEE802.1x support IEEE2600.1 compliant<sup>1)</sup>, Scan to Secure PDF</p> <p><sup>1)</sup> Optional</p> <p><sup>2)</sup> 1 GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m<sup>2</sup> if not otherwise mentioned.</p>

**OPTIONS**

**RADF – MR-3021**

100-sheet capacity, A5R-A3, 35-157 g/m<sup>2</sup>

**JOB SEPARATOR – MJ-5004**

2 inner trays, 150- and 250-sheet capacity

**OFFSET TRAY – MJ-5005**

250-sheet capacity

**INNER FINISHER – MJ-1032**

2 trays, 600-sheet capacity  
50-sheet multi-position stapling  
482 x 508 x 232 mm (W x D x H), ~ 13 kg

**SADDLE-STITCH FINISHER – MJ-1033**

1 tray, 1,000-sheet capacity  
50-sheet multi-position stapling  
Saddle-stitched booklets of up to 60 pages  
409 x 624 x 961 mm (W x D x H), ~ 39 kg

**HOLE PUNCH UNIT – MJ-6007/MJ-6008**

Options for Finisher MJ-1032/MJ-1033  
Available in 2 holes (E), 4 holes (F/S)  
120 x 245 x 597 mm (W x D x H), ~ 3.3 kg  
126 x 463 x 174 mm (W x D x H), ~ 3.4 kg

**PAPER FEED PEDESTAL – KD-1025**

550-sheet (1 drawer), A5R-A3, 64-105 g/m<sup>2</sup>  
668 x 701 x 291.5 mm (W x D x H), ~ 21 kg

**LARGE CAPACITY FEEDER – KD-1026A4**

2,000-sheet capacity, A4, 64-105 g/m<sup>2</sup>  
668 x 737 x 292 mm (W x D x H), ~ 25 kg

**OTHER OPTIONS**

- DESK – MH-2520
- DRAWER MODULE – MY-1033
- FAX BOARD – GD-1250EU-F
- DATA OVERWRITE ENABLER – GP-1070
- e-BRIDGE ID-GATE – KP-2004/5, TWN3XX
- WIRELESS LAN MODULE – GN-1060
- BLUETOOTH MODULE – GN-2020
- META SCAN ENABLER – GS-1010
- IPsec ENABLER – GP-1080
- UNICODE FONT ENABLER – GS-1007
- e-BRIDGE RE-RITE – GB-1280
- ACCESSIBILITY ARM – KK-2550
- DAMP HEATER KIT – MF-4550E

**TOSHIBA TEC GERMANY  
IMAGING SYSTEMS GMBH**

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS  
TEL. +49(0)2131-12450, FAX +49(0)2131-1245402  
WWW.TOSHIBA-EUROPE.COM/TEC

**TOSHIBA**  
Leading Innovation >>>

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2012 TOSHIBA TEC. DS-306SECBDD1202