



Colour Manager

- Extremely compact multifunctional colour system.
- Reliable productivity of up to 50 pages per minute.
- Excellent print quality and brilliant images.
- State-of-the-art document security thanks to Toshiba Secure HDD.
- Low power consumption for an economical and ecological business environment.

- e-STUDIO2555CSE**
- e-STUDIO3055CSE**
- e-STUDIO3555CSE**
- e-STUDIO4555CSE**
- e-STUDIO5055CSE**



SAP® Printer Vendor Solution





e-STUDIO2555CSE

e-STUDIO3055CSE

e-STUDIO3555CSE

e-STUDIO4555CSE

e-STUDIO5055CSE



General	<p>Print & Copy Speed 25/30/35/45/50 ppm (A4) 15/16/18/22/25 ppm (A3)</p> <p>Warm-up Time Approx. 12 seconds from low power mode</p> <p>Paper Size & Weight Cassette 1: A5R-A3, 60-256 g/m² Cassette 2: A5R-320 x 460 mm, 60-256 g/m² Bypass: 100 x 148 mm up to 320 x 460 mm, 52-280 g/m², banner paper (up to 305 x 1,200 mm, 90-163 g/m²)</p> <p>Paper Capacity 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Max. 3,200 sheets</p> <p>Automatic Duplex A5R-320 x 460 mm, 60-256 g/m²</p> <p>Inner Output Tray 400-sheet capacity</p> <p>Controller Type Toshiba e-BRIDGE</p> <p>Control Panel 9" (22.8 cm) colour touch panel LCD</p> <p>Memory Toshiba Secure HDD 160 GB²⁾/ 2 GB RAM</p> <p>Interface 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g/n) 585 x 644 x 787 mm ~ 75.5 kg</p>
Print	<p>Resolution Max. 600 x 600 dpi, 5 bit 600 x 1,200 dpi (1 bit, PostScript driver only)</p> <p>Page Description Language XPS, PCL 6 and PostScript 3 compatible</p> <p>Supported Systems Windows 8/7/Vista/XP/Server 2008/ Server 2003 (32/64 bit), Server 2012/Server 2008R2 (64 bit), Mac OS X 10.4.11-10.8, Linux/Unix, Citrix, Novell NetWare (NDPS), SAP, AS/400</p> <p>Colour Modes Auto-Colour (ACS), Colour, Twin Colour, B&W</p> <p>Colour Settings ICC profile colour management, Brightness, Saturation, Contrast, Colour Balance</p> <p>Print Functions Universal Driver, Templates, Driver plug-ins¹⁾, Print from USB, Hold print, Tandem printing</p>
Scan	<p>Resolution Max. 600 x 600 dpi</p> <p>Scan Speed Colour & B&W: up to 73 ipm (300 dpi)</p> <p>Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W, JPEG, Multi/Single Page TIFF/XPS/PDF, SecurePDF, Slim PDF, Searchable PDF¹⁾ (and other formats like DOCX, XLSX, RTF, TXT, PDF/A)¹⁾</p> <p>File Formats</p> <p>Scan Functions WS Scan, Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan¹⁾, Scan to Box (e-Filing), WIA, TWAIN</p>
Copy	<p>Resolution Scan: max. 600 x 600 dpi Print: max. 600 x 600 dpi</p> <p>First Copy Output Time Colour: Approx. 8.1/8.1/8.1/6.1/6.1 seconds B&W: Approx. 6.4/6.4/6.4/4.7/4.7 seconds</p> <p>Zoom 25-400% (platen), 25-200% (RADF)¹⁾</p> <p>Copy Modes Text, Text/Photo, Photo, Printed Image, Map, Image Smoothing</p> <p>Colour Modes Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&W</p> <p>Colour Settings Hue, Saturation, Colour Balance, 5 One-touch modes, RGB Adjustment</p> <p>Copy Functions Electronic sort, Rotate sort, ID card copy, Edge Erase, 2-in-1 / 4-in-1 mode</p>
Fax¹⁾	<p>Communication Super G3, G3, Internet Fax T.37</p> <p>Transmission Speed Approx. 3 seconds per page</p> <p>Compression JBIG, MMR, MR, MH</p> <p>Fax Memory 1 GB Transmission/Reception</p> <p>Network-Fax Driver Windows 8/7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Server 2012/Server 2008R2 (64 bit) To shared folders (SMB, FTP, IPX/SPX), E-Mail, e-Filing</p> <p>Incoming Fax Routing</p>
System & Security	<p>Device Management e-BRIDGE Fleet Management System¹⁾, Top Access for remote administration and configuration</p> <p>System Features e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan/Fax preview, Rip-while-Print, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip</p> <p>Accounting & Security Role Based Access, LDAP support, 1,000 department & 10,000 user codes, card reader¹⁾, private print, standard data encryption with Toshiba Secure HDD, Data Overwrite enabler¹⁾, IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant¹⁾, Scan to Secure PDF</p>

OPTIONS

- RADF – MR-3025**
100-sheet capacity, A5R-A3, 35-157 g/m²
- PLATEN COVER – KA-1640PC**
- PAPER FEED PEDESTAL – KD-1032-N**
550 sheets (1 cassette), A5R-A3⁴⁾, 60-256 g/m²
668 x 701 x 292 mm (W x D x H), ~ 16.3 kg
- DRAWER MODULE – MY-1039**
550 sheet cassette for PFP KD-1032-N,
A5R-A3⁴⁾, 60-256 g/m²
- LARGE CAPACITY FEEDER – KD-1031A4**
2,000-sheets capacity, A4, 64-105 g/m²
668 x 735 x 292 mm (W x D x H), ~ 25 kg
- INNER FINISHER – MJ-1036-N³⁾**
2 trays, 600-sheet capacity
50-sheet multi position stapling
A5R-A3, 60-105 g/m² (stapling mode)
482 x 508 x 232 mm (W x D x H), ~ 15.3 kg
- MULTI-STAPLING FINISHER – MJ-1107**
2 trays, 2,250-sheet capacity
50-sheet multi position stapling
A5R-A3, 60-105 g/m² (stapling mode)
535 x 598 x 1,092 mm (W x D x H), ~ 34 kg
- SADDLE STITCH FINISHER – MJ-1108**
2 trays, 3,250-sheet capacity
50-sheet multi position stapling
Saddle stitched booklets of up to 60 pages
A5R-A3, 60-105 g/m² (stapling mode)
617 x 603 x 1,085 mm (W x D x H), ~ 70 kg
- HOLE PUNCH UNIT – MJ-6007/ MJ-6104**
Option for Finisher MJ-1036-N/MJ-1107/
MJ-1108
Available in 2 holes, 4 holes
- OTHER OPTIONS**
- DESK – MH-2050
- JOB SEPARATOR – MJ-5006
- FAX BOARD – GD-1320EUX
- WIRELESS LAN MODULE – GN-1060
- e-BRIDGE ID-GATE – TWN3/4XX
- DATA OVERWRITE ENABLER – GP-1070
- IPsec ENABLER – GP-1080
- HARD COPY SECURITY KIT – GP-1190A
- META SCAN ENABLER – GS-1010
- UNICODE FONT ENABLER – GS-1007

¹⁾ optional
²⁾ 1GB = 1 billion bytes; the actual formatted capacity is less.
Available capacity will also be less if software applications
are pre-installed.
³⁾ e-STUDIO2555CSE/3055CSE/3555CSE only
⁴⁾ special format 320 x 460 mm possible

Productivity and paper specifications are related to a paper
size of A4 and a paper weight of 80 g/m²
if not otherwise mentioned.

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2013 Toshiba TEC. DS5055cseGBDD1307